

ARC addendum to plan approval

	Plan, plan and plan your indoor and outdoor lighting so there are no problems meeting the
	Dark Sky Lighting requirements. No glare of any light source is allowed beyond your property
	boundaries. Exterior & interior lighting must be approved by the ARC after fixtures are
	installed and at night. Approved by:Date:
	All recessed lighting in sloped ceilings must use fixtures that are designed for sloped ceilings
	(Halo H47ICAT or equivalent).
	All vents, chimneys, flashing etc. must be painted (flat) the color of the roof.
	All boxes, enclosure, vents etc. must be painted the body color of the house
	All plumbing vents must be located on the back roof and are not visible from the street.
	Consult with the ARC after roof is sheathed for approved placement of all roof
	perforations(vents, chimney's etc.). Approved by:Date:
	All propane tanks must be painted the body color of the house or concealed.
	All roof ventilation must be concealed within ridge/hip vents.
	The ARC approved plans (all copies) must be submitted for the building permit and must be
	kept on site for use by the builder, building inspector and by ARC members. When the
	building permit is approved submit a copy of the permit to Roy. Date received:
	All cutoff drains and foundation drains must be inspected and approved by Shade Tree Inc.
	before covering. No filter fabric allowed on a drain pipe/fixture.
	Approved by: Date:
	No more than 18inches (measured vertical) of foundation wall may be exposed.
	All protected trees must have fencing installed and inspected/approved by Shade Tree Inc.
_	before any construction/excavation is started. Contact Shade Tree Inc before fencing so they
	can determine where to place fence.
	Electric meter box must be recessed/flush, <1 inch protruding from siding and not exceeding
	15 inches wide and 34 inches high. Height of center of meter to be 5 feet above grade.
	Review the CC&R's and design guidelines so you don't have to make changes later in the
	building process. If you desire to make any changes on the exterior or lot grades after ARC
_	approval you must get ARC approval before proceeding.
	The exterior of the house, stonewalls, driveways, sidewalks, grade changes etc. must be
	completed one year from building permit issuance.
	Basalt walls must be all native from the site or all quarry, no mixing.
	Decks: Be sure deck plans are checked by an engineer as no X bracing is allowed.
	All notes, drawings and attachments by ARC take priority over all other drawing, notes etc.
<u>D</u> -	effective Windows also Cities Tries
K0	ofing colorWindow colorSidingTrim
	erhang Fascia Deck post size: Front Rear/sides
Heat pump decibel/bel ratingDistance from lot lineSatellite dish location	
So	
pai	nels:WaterElectricFireplaceChimneyVent
Bv	Date Lot#
KV	Date LOT#